

# Lessons learned towards safe and efficient wind turbine installations

A.J. VOOGT<sup>1</sup>, A.SREENIVASAN<sup>1</sup> and M.J. SAINT JAMES<sup>3</sup>

<sup>1</sup> MARIN, HOUSTON, TX USA <sup>2</sup> SAINT JAMES MARINE, ATLANTA, GA USA

## BACKGROUND

In a study funded by NOWRDC, MARIN studied the differences in the operability characteristics of various feeder concepts.

Saint James Marine provided project coordination and interface management with a large pool of stakeholders who provided input to the study and reviewed the results

## OBJECTIVE

Develop consensus-based best practice from collective knowledge, expertise & experience, to address a operability of feeder vessels

Identify the required minimum specification of feeder vessels to achieve acceptable availability.

## METHODS

A combination of time domain and frequency domain simulations provided a comparative operability for different feeder solutions.

Time domain simulations can handle changing draft/roll period, re-hits, winch speeds and details of non-linear hoist wire stiffness. The success rate was compared to the heave motions at the component foundations.


A frequency domain analysis quickly evaluates a range of feeder sizes, compensation systems, rails, roll mitigation to identify their impact on the driving vertical motions of the components during lift

## RESULTS


Feeder vessel with tower sections, blade rack and nacelle components to be lifted to Wind turbine Installation Vessel (WIV)



Simulations with time domain solver considering wave forces, hoist speed, component weight and hoist wire stiffness. These simulations were carried out with and without crane based heave compensation



Waves considered for operability are somewhat directional and mostly around 6 to 10 seconds peak period, predominantly between 1 and 2 meters




Re-hit is main driver of operability for component transfer

2 feet significant wave height for dominant wave periods

Crane based heave compensation helps

Deck based motion compensation also improves rigging

Advanced systems can increase wave height to 8 feet



Vessel	100m SS feeder		Barge feeder			165m SS feeder						
	No	Yes	No	Yes	Yes	No	Yes	Yes				
Roll	No	Yes	No	Yes	No	Yes	Yes	No	Yes	No	Yes	
Jan	39.8	45.2	46.2	48.4	48.4	48.4	52.7	54.8	68.8	75.3	80.6	81.7
Feb	43.5	45.9	48.2	49.4	42.4	43.5	44.7	47.1	80.0	84.7	85.9	87.1
Mar	48.4	49.5	52.7	57.0	50.5	52.7	57.0	57.0	79.6	81.7	84.9	87.1
Apr	37.8	45.6	47.8	52.2	42.2	47.8	56.7	57.8	67.8	73.3	80.0	82.2
May	59.1	66.7	74.2	77.4	63.4	66.7	71.0	75.3	77.4	80.6	88.2	89.2
Jun	87.8	94.4	95.6	96.7	87.8	92.2	95.6	95.6	100.0	100.0	100.0	100.0
Jul	86.5	91.9	93.2	94.6	83.8	91.9	91.9	91.9	97.3	97.3	97.3	97.3
Aug	83.9	85.5	88.7	88.7	87.1	87.1	88.7	90.3	93.5	93.5	95.2	96.8
Sep	53.3	63.3	63.3	66.7	56.7	60.0	63.3	63.3	71.7	78.3	80.0	80.0
Oct	32.3	35.5	48.4	50.0	35.5	40.3	46.8	51.6	66.1	67.7	67.7	71.0
Nov	51.7	56.7	60.0	60.0	58.3	63.3	66.7	66.7	78.3	83.3	85.0	86.7
Dec	43.5	50.0	50.0	56.5	48.4	50.0	53.2	56.5	66.1	69.4	77.4	79.0
Total	55.5	60.7	63.9	66.3	58.5	61.8	65.6	67.2	79.1	82.4	85.6	86.9

Operability is strongly seasonal in the U.S. northeast Atlantic coast.

Larger feeders vessels (>500ft) moored into the waves move less than feeder vessels of 300 ft length resulting in larger availability

Skidding and anti-roll systems improve operability somewhat in better wave conditions

## CONCLUSIONS

This study revealed the need for workforce development, modification to existing barges and new build vessels to match the demand and ensure an efficient and safe development. Installation contractors, designers and developers will participate to highlight the lessons learned from earlier installation projects

## ACKNOWLEDGEMENTS

We would like to acknowledge the National Offshore Wind Research and Development Consortium (NOWRDC) and funding provided to this project by New York State Energy Research and Development Authority (NYSERDA)

## REFERENCES

- [1] United States Government Accountability Office, Report to Congressional Committees, Offshore Wind Energy, December 2020 (GAO-21-153) <https://www.gao.gov/assets/gao-21-153.pdf>
- [2] United States Department of Energy, Offshore Wind Market Report: 2021 Edition [Offshore Wind Market Report: 2021 Edition \(energy.gov\)](https://www.energy.gov/offshore-wind-market-report-2021-edition)
- [3] World Forum Offshore Wind (WFO), Global Offshore Wind Report 2020 [WFO Global-Offshore-Wind-Report-2020.pdf \(wfo-global.org\)](https://www.wfo-global.org/global-offshore-wind-report-2020)
- [4] Rystad Energy, 2022. "Super-sized offshore wind installations could suffer bottlenecks from 2024 as vessels remain lightweight." Last modified February 2, 2022. <https://www.rystadenergy.com/newsevents/news/press-releases/Super-sized-offshore-wind-installations-could-suffer-bottlenecks-from-2024-as-vessels-remain-lightweight/>
- [5] United Kingdom Health & Safety Executive, Offshore Technology Report 2001/030, HSE: Wind and wave frequency distributions for sites around the British Isles
- [6] Offshore Wind Workshop, Offshore Wind Regulatory Framework, May 20, 2021. <https://www.bsee.gov/sites/bsee.gov/files/offshore-wind-regulatory-framework-ooc-may202021.pdf>
- [7] American Wind Energy Association, U.S. Offshore Wind Power Economic Impact Assessment, March 2020. [AWEA Offshore-Wind-Economic-ImpactsV3.pdf \(supportoffshorewind.org\)](https://www.awea.org/offshore-wind-economic-impacts-v3)
- [8] NOWRDC Project #107: Comparative Operability of Floating Feeder Solutions (M1.1)
- [9] NOWRDC Project #107: Operability Analysis Approach (M1.2)
- [10] NOWRDC Project #107: Consensus-based Document (M2.1), Guidance on Operability Analysis of Floating Feeder Solutions

## CONTACT INFORMATION

Arjan Voogt, [A.J.Voogt@marin.nl](mailto:A.J.Voogt@marin.nl), +1 832 305 6089